

FRP PRESSURE VESSEL DATASHEET-4 INCH END ENTRY

F40-1200E

ASME-certified, NSF-approved and CE-compliant models available

General Description	Technical Specifications	Unique Advantages
The First Line 40E Series is an 4-inch diameter pressure vessel with an end-entry design, engineered for commercial, municipal, and industrial reverse osmosis (RO) applications. *Standard element length = 40"	- Operating Pressure Options: 300 psi, 450 psi, 600 psi, 1000 psi, and 1200 psi. - Construction: High-strength epoxy/-glass composite for superior durability in continuous RO operations - Compatibility: Designed to accommodate all standard* 4" membrane elements.	- Robust construction ensures long-term reliability in demanding environments. - Various pressure ratings accommodate different water treatment needs. - Universal compatibility with industry-standard components.

TECHNICAL SPECIFICATIONS				
MODEL NUMBER	MAX. OPERATION PRESSURE	MAX. OPERATION TEMPERATURE	HYDROTEST PRESSURE	ELEMENT NUMBER
F40-1200E	1200 PSI / 83 bar	120 °F / 49 °C	1320 PSI / 91.5 bar	1-6

* Specifications are subjected to change without prior notice (for more details refer model specific engineering drawings)

Assembly Explosion View with Detailed Components



DRG REG	QTY	DESCRIPTION	MATERIAL	PART NUMBER
1	1	Shell	Epoxy FRP	As Required
2	4	O-ring , PWT	EPDM	20002478
3	4	O-ring , Head	EPDM	20002659
4	2	Sealing Plate	ABS	20002842
5	4	O-ring , F/C Port	EPDM	20000324
6	4	O-ring , Permeate Port	EPDM	20002430
7	2	Permeate Port	PPO	20002845
8	2	Bearing Plate	Aluminium Alloy	20003479
9	4	Connecting Bolt	304SST	20000439
10	4	Retaining Ring	304SST	20000657
11	2	Feed/Conc. Port	2507SST	20000428
12	6	Locking Kit Segment	316SST	20000013/14/15
13	6	Locking Kit Screw	304SST	20000205
14	1	Plug	PPO	20003046